

Data Sheet

1209 4½" SS Process Gauge

FEATURES

- Solid front case design with full pressure relief back
- 4½" Dial size
- Accuracy: ±0.50% of span (ASME B40.100 Grade 2A)
- 316L SS case and ring
- Patented **PLUS!**™ Performance
Dampens vibration, shock and pulsation effects

TYPICAL USES

- Oil & Gas Industry
Upstream: Onshore/offshore production
Midstream: Transport, storage and natural gas compression
Downstream: Refineries and petrochemical industries
- Chemical Industry
- Injection molding equipment
- Power Plants
Conventional power plants
Nuclear power plants
Flue gas desulfurization plants
- Other Industries
Waste incineration plants
Seawater desalination plants
Steel mills
Cement plants



1209
4½" Dial size

KEY BENEFITS

- Full pressure relief back for safety
- Socket welded to case for superior leak integrity

SPECIFICATIONS

Accuracy:	±0.5% of span (ASME B40.100 Grade 2A)
Dial Size:	4½"
Process Connection:	¼ NPT, ½ NPT
Case Style:	Solid front with full pressure relief back
Movement:	Adjustable
Window Material:	Glass (STD.)
Pointer:	Aluminum
Weather Protection:	IP65 hermetically sealed
Mounting:	Stem
Dampening:	Liquid fill, PLUS! ™ Performance, throttle screw, dampeners, capillary, diaphragm seals and snubbers

WETTED COMPONENTS

Model	Bourdon Tube	Process Connection	Joints
1209	316L SS	316L SS	Welded

NON-WETTED COMPONENTS

Model	Case	Ring	Back Cover
1209	316L SS	316L SS	316L SS

MIN./MAX. TEMPERATURE LIMITS

	Ambient	Process	Storage
Dry	-40 to 200°F (-40 to 93°C)	-40 to 200°F (-40 to 93°C)	-40 to 200°F (-40 to 93°C)
PLUS! ™	-40 to 200°F (-40 to 93°C)	-40 to 200°F (-40 to 93°C)	-40 to 200°F (-40 to 93°C)
Glycerin	20 to 150°F (-7 to 66°C)	20 to 150°F (-7 to 66°C)	20 to 150°F (-7 to 66°C)
Silicone	-40 to 150°F (-40 to 66°C)	-40 to 150°F (-40 to 66°C)	-40 to 150°F (-40 to 66°C)
Halocarbon®	-40 to 150°F (-40 to 66°C)	-40 to 150°F (-40 to 66°C)	-40 to 150°F (-40 to 66°C)

Note: Other than discoloration of the dial and hardening of the gasketing that may occur as ambient or process temperatures exceeds 150°F, non-liquid-filled gauges with standard glass windows, can withstand continuous operating temperatures up to 250°F (121°C). Liquid-filled gauges can withstand 200°F (93°C) but glycerin fill and acrylic window will tend to yellow. Accuracy at temperatures above or below the reference ambient temperature of 68°F (20°C) will be affected by approximately 0.4% per 25°F. Gauges with welded joints will withstand 750°F (400°C), 450°F (232°C) with silver brazed joints for short times without rupture, although other parts of the gauge will be destroyed and calibration will be lost. For continuous use and for process or ambient temperatures above 250°F (121°C), a diaphragm seal or capillary or siphon is recommended.

OPTIONAL FEATURES

Window:	Safety glass, acrylic
Pointer:	Max. adjustable
Tag Options:	SS, wired to cover
Stop Options:	Overload, underload
Material Test Report:	EN 10204.3.1
Consult Factory For:	Individual calibration charts and cleaned for oxygen services

Data Sheet

1209 4½" SS Process Gauge

ORDERING CODE	Example:	451209	S	D	04	L	15#	-XLL
Dial Size/Model Code								
451209 - 4½" SS, solid front process gauge per ASME B40.100		451209						
System (tube and process connection)								
S - SS system			S					
Case Fill								
D - Dry Case				D				
L - Liquid filled case, glycerin (STD.)								
Process Connection Sizes								
02 - ¼ NPT Male (up to 20,000 psi)								
04 - ½ NPT Male (up to 20,000 psi)					04			
Process Connection Location								
L - Lower connection only						L		
Range (coding examples only, see range table on next page for all standard ranges)								
Single Scales								
15# - 15 psi							15#	
1KSC - 1 kg/cm ²								
100KP - 100 kPa								
Options (if choosing an option(s) must include an "X")								
EP - Maximum pointer, adjustable								-X__
LL - <i>PLUS!</i> ™ Performance								LL
NH - SS tag wired to case								
OS - Overload stop								
PD - Acrylic window								
SG - Safety glass								
VS - Underload stop								
C3 - Material test report to EN 10204.3.1								
C4 - Individual calibration chart (in accordance with ASME B40.100:2013. Accuracy traceable to NIST)								
6B - Cleaned for oxygen service								

Data Sheet

1209 4 1/2" SS Process Gauge

1209 STANDARD RANGES						
	psi	bar	kPa	mPa	kg/cm ²	
Vacuum	30IMV	N1BR	N100KP	N1MP	N1KG	
	-	N1/0.6BR	N100/60KP	0.1/0.06MP	N1/0.6KG	
Compound	V/15#	-	-	-	-	
	-	N1/1.5BR	N100/150KP	N0.1/0.15MP	N1/1.5KG	
	V/30#	-	-	-	-	
	-	N1/3BR	N100/300KP	N0.1/0.3MP	N1/3KG	
	V/60#	-	-	-	-	
	-	N1/5BR	N100/500KP	N0.1/5MP	N1/5KG	
	V/100#	-	-	-	-	
	-	N1/9BR	N100/900KP	N0.1/0.9MP	N1/9KG	
	Positive Pressure	15#	1BR	100KP	0.1MP	1KG
		20#	-	-	-	-
-		1.6BR	160KP	0.16MP	1.6KG	
30#		-	-	-	-	
-		2.5BR	250KP	0.25MP	2.5KG	
60#		4BR	400KP	0.4MP	4KG	
-		6BR	600KP	0.6MP	6KG	
100#		-	-	-	-	
120#		-	-	-	-	
-		10BR	1000KP	1MP	10KG	
160#		-	-	-	-	
200#		-	-	-	-	
-		16BR	1600KP	1.6MP	16KG	
300#		-	-	-	-	
-		25BR	2500KP	2.5MP	25KG	
400#		-	-	-	-	
500#		-	-	-	-	
600#		40BR	4000KP	4MP	40KG	
800#		-	-	-	-	
-		60BR	6000KP	6MP	60KG	
1000#	-	-	-	-		
1500#	100BR	10000KP	10MP	100KG		
2000#	-	-	-	-		
-	160BR	16000KP	16MP	160KG		
3000#	-	-	-	-		
-	250BR	25000KP	25MP	250KG		
4000#	-	-	-	-		
5000#	-	-	-	-		
6000#	400BR	40000KP	40MP	400KG		
8000#	-	-	-	-		
-	600BR	60000KP	60MP	600KG		
10000#	-	-	-	-		
15000#	1000BR	100000KP	100MP	1000KG		
20000#	1600BR	-	160MP	1600KG		

DIMENSIONS in [] are millimeters

