

## C1091 Gauge valve

### Applications

- Be used to shut down or block the liquid medium, natural gas or steam, and so on...
- Different material can deal with corrosive medium and harsh environments
- Can be applied in different process industries such as machinery manufacturing, petrochemicals, power plants, environmental protection, and offshore platforms

### Features

- Maximum Pressure rating : PN420(6000 psi)
- Variety of material are available to meet your needs
- With vent



### Ordering Code C1091 - S -50 -04 - NH

Model		
C1091	Gauge valve	C1091
Material		
S	316SS	S
M	Monel	M
H	Hastelloy C	H
J	Duplex	J
Instrument Connection Size		
25	1/4 NPT Female	25
50	1/2 NPT Female	50
27	G1/4 Female	27
51	G1/2 Female	51
02	1/4 NPT Male	02
04	1/2 NPT Male	04
06	3/4 NPT Male	06
13	G1/4 Male	13
15	G1/2 Male	15
Process Connection Size		
25	1/4 NPT Female	25
50	1/2 NPT Female	50
27	G1/4 Female	27
51	G1/2 Female	51
02	1/4 NPT Male	02
04	1/2 NPT Male	04
13	G1/4 Male	13
15	G1/2 Male	15
Options		
NH	With tags	NH
VT	With 1/4NPT vent	VT

### Specifications

#### Wetted parts material

316L, Monel, Hastelloy C276

Othe material see code list

#### Connection Size

Instrument Connection G1/2 Female, 1/2NPT Female  
Other connection see code list

Process Connection G1/2 Male, 1/2NPT Male  
Other connection see code list

#### Vent

Connection size 1/4 NPT with plug