

C1092 2-Valve Manifold

- Be used to shut down or block the liquid medium, natural gas or steam, and so on...
- Different material can deal with corrosive medium and harsh environments
- Can be applied in different process industries such as machinery manufacturing, petrochemicals, power plants, environmental protection, and offshore platforms



C1092 2-Valve Manifold

Specifications

Wetted parts material

316L, Monel, Hastelloy® C-276
 Other material see code list

Connection Size

Instrument Connection G1/2 Female, 1/2NPT Female
 Other connection see code list

Process Connection G1/2 Male, 1/2NPT Male
 Other connection see code list

Vent

Connection size 1/4 NPT with plug

KEY BENEFITS

- Maximum Pressure rating : PN420(6000 psi)
- Variety of material are available to meet your needs
- With vent

Ordering Code C1092 - S -50 -04 - NH

Model

C1092 | 2-Valve Manifold C1092

Material

S	316SS	S
M	Monel	M
H	Hastelloy® C	H
J	Duplex	J

Instrument Connection Size

25	1/4 NPT Female	25
50	1/2 NPT Female	50
27	G1/4 Female	27
51	G1/2 Female	51
02	1/4 NPT Male	02
04	1/2 NPT Male	04
06	3/4 NPT Male	06
13	G1/4 Male	13
15	G1/2 Male	15

Process Connection Size

25	1/4 NPT Female	25
50	1/2 NPT Female	50
27	G1/4 Female	27
51	G1/2 Female	51
02	1/4 NPT Male	02
04	1/2 NPT Male	04
13	G1/4 Male	13
15	G1/2 Male	15

Options

NH	With tags	NH
MO	Assembled before shipping	MO