

1005P XUL Fire Protection Sprinkler Service Gauge

Features

- PowerFlex™ movement provides superior resistance to shock, vibration and pulsation
- TrueZero™ reduces reading errors by using a “zero box” instead of conventional dial pins
- Water or Air gauges available for wet/dry
- Heat-resistant polycarbonate push-in window
- Custom dials available

Typical Uses

- Fire Sprinklers for water or air systems

Specifications

Accuracy:	±3-2-3% of span (ASME B40.100 Grade B)
Sizes:	3½"
Ranges:	Single, dual or triple scale 0-300 psi (water) 0-80 psi retard to 250 psi (air) 0-600 psi
Process Connection Location:	Lower
Process Connection Size:	¼ NPT
Dial:	Black figures on white background
Pointer:	Black, aluminum
Weather Protection:	Weather resistant
Movement:	PowerFlex™ with Brass/polyester segment
Approvals:	UL 393 listed for fire protection sprinkler service UL Canada listed FM approved

Wetted Components

Bourdon Tube	Process Connection
Bronze	Brass

Non-Wetted Components

Case	Window
ABS (Polycarbonate blend)	Polycarbonate



1005P XUL
3½" dial size

Key Benefits

- Single scale, dual scale and triple scale dials available (bar, kPa, psi)
- Corrosion resistant ABS case
- Custom Dials available

Min/Max Temperature Limits

Version	Ambient	Process	Storage
1005P XUL	-40 °F to 150 °F (-40 °C to 65 °C)	-40 °F to 150 °F (-40 °C to 65 °C)	-40 °F to 150 °F (-40 °C to 65 °C)

Contact Us

1.800.328.8258
ashcroft.com

All specifications are subject to change without notice. All sales subject to standard terms and conditions.
 Ashcroft®, FlutterGuard™, PowerFlex™, TrueZero™ and Trust the Shield® are trademarks of Ashcroft Inc.
 Refer to [Ashcroft Brands & Trademarks](#) ©2026 Ashcroft Inc. 1005p-xul_gauge_ds_RevC_26-May-26

1005P XUL Fire Protection Sprinkler Service Gauge

Ordering Code	Example:	35	W	1005	P	H	02	L	XULZO	100#
Dial Size										
35 - 3 1/2"		35								
Movement type										
W - PowerFlex™			W							
Model										
1005				1005						
Case/Window Material										
P - ABS/Polycarbonate					P					
Process Connection Material										
H - Brass						H				
Process Connection Size										
02 - 1/4 NPT							02			
Process Connection Location										
L - Lower								L		
Options - Minimums apply for optional features (If choosing an options(s) must include "X")									X__	
UL - (required - UL393 listed and FM approved)									UL	
Packaging/Labeling										
ZO - Bulk pack									ZO	
ZP - Customer part number on carton/plain white label										
ZQ - Customer part number printed directly on carton										
Ranges										
Single Scale										
100# - 0/80 psi retard to 250 psi outer scale										100#
300# - 0/300 psi outer scale										
600# - 0/600 psi outer scale										
Dual Scale (psi/kPa)										
100# - AGN - 0/80 psi retard to 250 psi outer scale; 0/550 kPa retard to 1750 kPa inner scale										
300# - AGS - 0/300 psi outer scale; 0/2000 kPa inner scale										
600# - AGV - 0/600 psi outer scale; 0/4000 kPa inner scale										
Triple Scale (psi/kPa/bar)										
100# - CAA - 0/80 psi retard to 250 psi outer scale; 0/550 kPa retard to 1750 kPa middle scale; 0/5.5 bar retard to 17.5 bar inner scale										
300# - CAB - 0/300 psi outer scale; 0/2000 kPa middle scale; 0/20 bar inner scale										

1005P XUL Fire Protection Sprinkler Service Gauge

Dimensions

For reference only, consult Ashcroft for specific dimensional drawings

Lower Connection							
Dial Size inches	A	B	C	D	E	G	Weight
3½"	3.70 [94]	1.14 [29]	2.72 [69]	3.61 [92]	0.47 [11.0]	0.56 [14.2]	5.36 oz 0.152 kg

