

## DSPT Plastic Seal

### Features

- Wetted components are of full plastic construction
- No metallic wetted parts
- Process connections may adopt direct threaded connection, bonding or hot fusion joining

### Typical Uses

- Chemical Industry
- Electroplating Industry
- Wastewater Treatment
- Fertilizer Industry
- Other low-pressure, highly corrosive process conditions



### Key Benefits

- Non-metallic wetted materials
- Applicable to highly corrosive process media

### Specifications

<b>Wetted Materials</b>	
Diaphragm:	PTFE
Housing:	PVC / PTFE Top housing 316L SS, Lower housing PTFE
<b>Connection</b>	
Instrument Connection:	G1/2 Female, G1/4 Female
Process Connection:	G1/2, G1/4, 1/2 NPT, 1/4 NPT, G3/8, 3/8 NPT
<b>Range</b>	
Gauge Range :	0~0.6 MPa to 0~1 MPa

### Contact Us




- ☎ 400 - 187 - 6586
- 🌐 [www.ashcroft.com.cn](http://www.ashcroft.com.cn)
- ✉ [sales@ashcroft.com.cn](mailto:sales@ashcroft.com.cn)

All specifications are subject to change without notice. All sales subject to standard terms and conditions. Ashcroft® and Trust the Shield® are trademarks of Ashcroft Inc.  
©2026 Ashcroft\_CN. DSPT\_en\_RevB\_29-Apr-26

## DSPT Plastic Seal

Ordering Code		Example:	04	DSPT	T	V	13T	CK	NH
<b>Process Connection</b>									
04	1/2 NPT Male		04						
18	G1/2 Male		18						
16	M20×1.5 Male		16						
02	1/4 NPT Male		02						
13	G1/4 Male		13						
25	1/4 NPT Female		25						
26	G1/4 Female		26						
50	1/2 NPT Female		50						
51	G1/2 Female		51						
<b>Model</b>									
DSPT	Plastic Seal			DSPT					
<b>Diaphragm Material</b>									
T	PTFE				T				
<b>Housing Material</b>									
V	PVC					V			
T	PTFE					T			
SV	Top housing 316 SS, Lower housing PVC					SV			
<b>Instrument Connection</b>									
13T	G1/4 Female						13T		
51T	G1/2 Female						51T		
<b>Filling Oil</b>									
CK	Silicone							CK	
<b>Other Options</b>									
MO	Mount on Instrument								MO
NH	Tag								NH
6W	Cleaned for oxidizing processes other than Oxygen								6W

### Contact Us

 400 - 187 - 6586  
 [www.ashcroft.com.cn](http://www.ashcroft.com.cn)  
 [sales@ashcroft.com.cn](mailto:sales@ashcroft.com.cn)

All specifications are subject to change without notice. All sales subject to standard terms and conditions. Ashcroft® and Trust the Shield® are trademarks of Ashcroft Inc.  
 ©2026 Ashcroft\_CN. DSPT\_en\_RevB\_29-Apr-26